


SEVEN DARLINGTON ARRAYS

- SEVEN DARLINGTONS PER PACKAGE
- OUTPUT CURRENT 500 mA PER DRIVER (600 mA PEAK)
- OUTPUT VOLTAGE 50 V
- INTEGRAL SUPPRESSION DIODES FOR INDUCTIVE LOADS
- OUTPUT CAN BE PARRALLELED FOR HIGHER CURRENT
- TTL/CMOS/PMOS/DTL COMPATIBLE INPUTS
- INPUTS PINNED OPPOSITE OUTPUTS TO SIMPLIFY LAYOUT



DESCRIPTION

The ULQ2001R, ULQ2002R, ULQ2003R and ULQ2004R are high voltage, high current darlington arrays each containing seven open collector darlington pairs with common emitters. Each channel is rated at 500 mA and can withstand peak currents of 600 mA. Suppression diodes are included for inductive load driving and the inputs are pinned opposite the outputs to simplify board layout.

The four versions interface to all common families.

ULQ2001R General Purpose, DTL, TTL, CMOS

ULQ2002R 15-25 V PMOS

ULQ2003R 5 V TTL, CMOS

ULQ2004R 6-15 V CMOS, PMOS


These versatile devices are useful for driving a wide range of loads including solenoids, relays DC motors, LED displays, filament lamps, thermal printheads and high power buffers.

The ULQ2001R, ULQ2002R, ULQ2003R and ULQ2004R are supplied in 16 pin ceramic DIP packages.





ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_o	Output Voltage	50	V
V_{in}	Input Voltage (for ULQ2002R/2003R/2004R)	30	V
I_c	Continuous Collector Current	500	mA
I_b	Continuous Base Current	25	mA
T_{amb}	Operating Ambient Temperature Range	- 20 to + 85	C
T_{sig}	Storage Temperature Range	- 55 to 150	C

PIN CONNECTION



SCHEMATIC DIAGRAM

Series ULQ2001R
(each driver)Series ULQ2002R
(each driver)Series ULQ2003R
(each driver)Series ULQ2004R
(each driver)

THERMAL DATA

$R_{th(j-amb)}$	Thermal Resistance Junction-ambient	Max	150	°C/W
-----------------	-------------------------------------	-----	-----	------

ELECTRICAL CHARACTERISTICS ($T_{amb} = 25^\circ C$ unless otherwise specified)

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Unit	Fig.
I_{CEX}	Output Leakage Current	$V_{CE} = 50 V$	$T_{amb} = 70^\circ C$	$V_{CE} = 50 V$		50	μA	1a
		$T_{amb} = 70^\circ C$				100	μA	1a
		for ULQ2002R						
		$V_{CE} = 50 V$	$V_i = 6 V$			500	μA	1b
$V_{CE(sat)}$	Collector-emitter Saturation Voltage	$V_{CE} = 50 V$	$V_i = 1 V$			500	μA	1b
		$I_C = 100 mA$	$I_B = 250 \mu A$		0.9	1.1	V	2
		$I_C = 200 mA$	$I_B = 350 \mu A$		1.1	1.3	V	2
$I_{i(on)}$	Input Current	$I_C = 350 mA$	$I_B = 500 \mu A$		1.3	1.6	V	2
		for ULQ2002R		$V_i = 17 V$	0.82	1.25	mA	3
		for ULQ2003R		$V_i = 3.85 V$	0.93	1.35	mA	3
		for ULQ2004R		$V_i = 5 V$	0.35	0.5	mA	3
$I_{i(off)}$	Input Current	$V_{CE} = 2 V$			1	1.45	mA	3
		$T_{amb} = 70^\circ C$	$I_C = 500 \mu A$	50	65		μA	4
$V_{i(on)}$	Input Voltage	for ULQ2002R						
		$V_{CE} = 2 V$	$I_C = 300 mA$			13	V	5
		for ULQ2003R						
		$V_{CE} = 2 V$	$I_C = 200 mA$			2.4	V	5
		$V_{CE} = 2 V$	$I_C = 250 mA$			2.7	V	5
		$V_{CE} = 2 V$	$I_C = 300 mA$			3	V	5
		for ULQ2004R						
		$V_{CE} = 2 V$	$I_C = 125 mA$			5	V	
		$V_{CE} = 2 V$	$I_C = 200 mA$			6	V	5
		$V_{CE} = 2 V$	$I_C = 275 mA$			7	V	5
h_{FE}	DC Forward Current Gain	$V_{CE} = 2 V$		$I_C = 350 mA$	1000		-	2
C_i	Input Capacitance				15	25	pF	-
t_{PLH}	Turn-on Delay Time	$0.5 V_i$ to $0.5 V_o$			0.25	1	μs	-
t_{PHL}	Turn-off Delay Time	$0.5 V_i$ to $0.5 V_o$			0.25	1	μs	-
I_R	Clamp Diode Leakage Current	$V_R = 50 V$			50	μA	6	
		$T_{amb} = 70^\circ C$	$V_R = 50 V$		100	μA	6	
V_F	Clamp Diode Forward Voltage	$I_F = 350 mA$			1.7	2	V	7

TEST CIRCUITS

Figure 1a.




Figure 1b.




Figure 2.




Figure 3.




Figure 4.




Figure 5.




Figure 6.




Figure 7.

