



**Data Sheet** 

# Barracuda<sup>®</sup> Green

Green power that will not slow you down

# 2 TB, 1.5 TB and 1 TB • SATA 6 Gb/s and SATA 3 Gb/s

### **Key Advantages**

- A unique 5,900 RPM platform that delivers the fastest performance of any eco-friendly drive available
- Seagate SmartAlign<sup>™</sup> technology provides the benefits of the new Advanced Format 4K sector standard without the hassle — no utilities, no extra steps
- Plenty of capacity for storage-hungry applications
- The SATA 6 Gb/s interface and 64 MB cache maximise performance, especially in cache-intensive applications
- Low power consumption, combined with leadership in the use of materials that conform to environmental compliance programmes, means you do not have to sacrifice environmental stewardship for performance
- Cool, quiet operation

### **Best-fit Applications**

- High-capacity desktop storage
- Direct Attached Storage devices: USB/FireWire/eSATA
- Network Attached Storage devices and Windows storage servers
- Eco-friendly PCs







# Barracuda® Green

## Green power that will not slow you down



#### **Barracuda Green Drives Save Time**

The Seagate<sup>®</sup> Barracuda Green drive saves you time with a combination of fast performance and no-hassle hard drive integration.

- Delivering a sustained data throughput of up to 144 MB/s, the Barracuda Green drive sets a new standard for performance in the eco-drive category.
- Seagate SmartAlign technology delivers a new level of simplicity for Advanced Format 4K drives. While other Advanced Format drives require the use of additional software utilities during integration, the Barracuda Green drive with Seagate SmartAlign technology requires no extra time or steps.

The Barracuda Green drive fulfils the product promise — Green power that will not slow you down!

#### seagate.com Toll free: 00 8004 SEAGATE (732 4283) (non toll free: 001 405 324 4714)

Specification	2 TB <sup>1</sup>	1.5 TB <sup>1</sup>	1 TB <sup>1</sup>
Model Number	ST2000DL003	ST1500DL003	ST1000DL002
Interface Options	SATA 6 Gb/s NCQ	SATA 6 Gb/s NCQ	SATA 3 Gb/s NCQ
Performance			
Spindle Speed (RPM)	5,900	5,900	5,900
Cache, Multi-segmented (MB)	64	64	32
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	3.0/1.5
Average Latency (ms)	4.16	4.16	4.16
Average Seek, Typical Read (ms)	12	12	12
Average Seek, Typical Write (ms)	13	13	13
Power On to Ready (sec)	<17	<17	<17
Sustained Data Rate OD (MB/s)	144	144	144
Configuration/Organisation			
Bytes per Sector	4,096	4,096	4,096
Voltage			
Voltage Tolerance, Including Noise (5V)	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%
Voltage Tolerance, Including Noise (12V)	+10%/-7.5%	+10%/-7.5%	+10%/-7.5%
Reliability/Data Integrity			
Load/Unload Cycles (25°C, 50% Humidity)	300,000	300,000	300,000
Non-recoverable Read Errors per Bits Read, Max	1 per 1014	1 per 1014	1 per 1014
Annualised Failure Rate (AFR)	0.34%	0.34%	0.34%
Limited Warranty (years)	3	3	3
Power Management			
Operating Mode, Typical (W)	5.8	5.8	5.8
Idling Mode (W)	4.5	4.5	4.5
Standby Mode (W)	0.5	0.5	0.5
Sleep Mode (W)	0.5	0.5	0.5
Start-up Current +12V Peak (A, ±10%)	2.0	2.0	2.0
Environmental			
Temperature			
Operating (°C)	0 to 60	0 to 60	0 to 60
Non-operating (°C)	-40 to 70	-40 to 70	-40 to 70
Shock			
Operating, 2ms (Gs)	80	80	80
Non-operating, 2ms (Gs)	300	300	300
Physical			
Height (mm/in)	26.1/1.028	26.1/1.028	26.1/1.028
Width (mm/in)	101.6/4.0	101.6/4.0	101.6/4.0
Depth (mm/in)	147.00/5.78	147.00/5.78	147.00/5.78
Weight (g/lb)	635/1.39	635/1.39	635/1.39

<sup>1</sup> One gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

AMERICAS ASIA/PACIFIC EUROPE, MIDDLE EAST AND AFRICA Seagate Technology LLC 920 Disc Drive, Scotts Valley, California 95066, United States, +1 831 438 6550 Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888 Seagate Technology SAS 16-18 rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

© 2011 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Barracuda, Seagate Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks or segate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks or gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1726.1-1101GB, January 2011